

SANDSUN
山田順精機

QUICK DIE / MOLD CHANGE SYSTEM

快速換模/台車系統

MOLD FLIP DEVICE
OVERLOAD PROTECTOR
AIR DRIVEN HYDRAULIC PUMP
P.C. BOARD PIERCING SYSTEM



模具翻轉機
氣動油壓泵浦
超負荷保護裝置
印刷電路板沖孔脫料系統

快速換模 / 台車系統

QUICK DIE / MOLD CHANGE SYSTEM

APPLICATION 適用

- Press / 沖床
- Injection Molding Machine / 射出機
- Die Casting Machine / 壓鑄機
- Hydraulic Press / 油壓機
- Blow Molding Machine / 中空成型機



Die Clamp / 夾具



CA



CB



CE.CF



CAA



CB-C



CG



CD




CAR

Die Lifter / 舉模滑軌



DL



DS

DLS

Die Arm / 移模支臂



RS



RC

RD

RE.RF

OVERLOAD PROTECTOR FOR PRESS 沖床超負荷保護裝置



- Suitable for press capacity from 25 to 2000 tons.
- Used to check the overload hydraulic pressure of cylinder inside press slide.
- It helps to release the hydraulic pressure of cylinder immediately within 3/1000 seconds.
- When overload happens, the electric signal would be released to stop machine from working for protection of the press and die.
- Air driven hydraulic pump is able to supply the hydraulic pressure to cylinder in a short time.
- Overload protector is equipped with pressure control valve which adjusts the hydraulic pressure automatically with oil temperature arising.

- 適用沖床噸數: 25~2000噸。
- 用以檢知滑塊油壓缸內部的超負荷油壓壓力。
- 使油壓壓力能在千分之三秒內迅速被洩放。
- 超負荷時產生電氣信號，通知沖床緊急停止，以保護沖床和模具。
- 氣動油壓泵浦能快速補足油壓壓力。
- 超負荷保護裝置內具有恆壓控制閥，自動調節溫度上升所受的影響。

AIR DRIVEN HYDRAULIC PUMP UNIT 氣動油壓泵浦單元




- The hydraulic pump is driven by air. Once the hydraulic pressure reaches the pressure setting, it stops pumping.
- The pump would supply pressure automatically if the working pressure reduces.
- Capable of pressure inspection and interlocking with machines.
- Various hydraulic pressure (60-500 kg/cm²) for choice based on requirement.
- The circuit control system is with the function of checking and avoiding oil leakage.

- 利用空氣壓力驅動泵浦，出口油壓達設定壓力即停止。
- 泵浦壓力降時自動補壓功能。
- 具壓力檢知功能，可與機台連線。
- 可依需要搭配不同出力(60~500kg/cm²)。
- 迴路控制系統具逆止防漏功能。

P.C. BOARD PIERCING SYSTEM 印刷電路板沖孔脫料系統

POWER UNIT
油壓動力單元



PIERCING PLATE
脫料台盤

- This system employs hydraulic pressure to activate the plate to knock out in order to prevent the board and dies from strong hits and avoid breaking of pierce pins.
- Simple adjustment of the operating pressure for knock-out and holder is acceptable according to the material and specification of P.C. boards.
- Holder function is provided in order to avoid cracking, flaking and burr during piercing.
- Quick die change system is equipped in order to shorten dies changing time and ensure working safety.

- 利用油壓原理脫料，可避免板材、模具受撞擊，並減少沖針斷裂。
- 脫料及壓板使用壓力，可依PC板之規格、材質作簡易的調整。
- 具壓板功能，可避免沖孔時造成龜裂。
- 搭配快速換模系統，可縮短換模時間，確保安全性。

MOLD FLIP DEVICE 模具翻轉機



MOLD CHANGER SYSTEM 換機台車系統**INSTALLATION PHOTO FOR MOLD CHANGER SYSTEM** 台車實際安裝照片**CONTROL OPERATION PANEL** 電控操作箱

QDC



QMC





SANDSUN ISO 9001 CE

MANAGING PHILOSOPHY

Moderate & Reliable Aggressive & Creative
Demanding for Perfection Constant Operation

QUALITY POLICY

Quality Stability Customer Satisfaction

經營理念

穩健踏實 精進創新 止於至善 永續經營

品質政策

品質穩定 客戶肯定

山田順精機股份有限公司

SANDSUN PRECISION MACHINERY CO.,LTD.

台灣彰化縣大村鄉中山路三段57巷7號
NO.7, LANE 57, SEC.3, CHUNG-SHAN RD., DAH-TSUEN,
CHANG-HWA, TAIWAN.

E-mail:sa2@sandsun.com.tw (台灣)
sa3@sandsun.com.tw (abroad)
sa4@sandsun.com.tw (abroad)
TEL:+886-4-8536688 FAX:+886-4-8536699

山田順精密機械(蘇州)有限公司

SANDSUN PRECISION MACHINERY (SUZHOU) CO.,LTD.

江蘇省蘇州市吳中區甪直鎮楓莊路
Fengzhuang Road, LuZhi Town, WuZhong District,
SuZhou City,JiangSu, China

E-mail:sandsun_sz@126.com
TEL:0512-66026635 FAX:0512-66026637

www.sandsun.com.tw

